


Beyond the Ordinary



Printing for Professionals

Océ VarioPrint 6000 Technology and Awards*



Golden Medal 2007,
Poznań International Fair
(Europe)



Best of Show Award
2006, On Demand
(USA)



InterTech Technology Award
2007, Printing Industries of
America/Graphic Arts Technical
Foundation (USA)

*Awarded 2008, 2007, 2006

All rights, including rights created by patent grant or registration of a utility model or design are reserved. Delivery subject to availability, subject to change for technical reasons. All hardware and software names are trade names or trademarks of their respective manufacturers. Specifications subject to change without notice. Copyright 2009, Océ North America, Inc.

About Océ

Océ is a leading international provider of digital document management technology and services. The company's solutions are based on Océ's advanced software applications that deliver documents and data over internal networks and the Internet to printing devices and archives – locally and around the world. Supporting the workflow solutions are Océ digital printers and scanners, considered the most reliable and productive in the world. Océ also offers a wide range of display graphics, consulting and outsourcing solutions.

Océ employs around 23,000 people, with 2008 revenues of approximately \$4.3 billion, operates in around 100 countries and maintains research and manufacturing centers in the Netherlands, the United States, Canada, Germany, France, Belgium, the Czech Republic, Romania and Singapore. Océ North America is headquartered in Trumbull, CT, with additional business units in Chicago, IL; New York City; Boca Raton, FL; Salt Lake City, UT and Vancouver, BC. North American revenues represented approximately half of Océ's worldwide business in 2008, and employment is approximately 10,000. For more information about Océ, visit www.oceusa.com. Outside the U.S., consult <http://global.oce.com>.

Océ North America

Production Printing Systems

5600 Broken Sound Boulevard
Boca Raton, FL 33487
1.800.523.5444

Document Printing Systems

100 Oakview Drive
Trumbull, CT 06611
1.800.523.5444

www.oceusa.com

3002-08/09



Océ VarioPrint® 6000 Ultra Line

Experience ultra speed



Ultra-high-speed digital perfecting systems

Ready to take your cutsheet printing performance to new heights? Meet the Océ VarioPrint® 6000 Ultra Line, the world's fastest and most productive family of digital perfecting systems. Choose from four models: the Océ VarioPrint 6320 Ultra, the Océ VarioPrint 6250 Ultra, the Océ VarioPrint 6200 Ultra and the Océ VarioPrint 6160 Ultra. All are powered by Océ Gemini Instant Duplex™ technology for unmatched power and scalability at speeds of 166, 200, 250 or 306 letter duplex prints per minute.

General

- Océ Gemini Instant Duplex technology
- Advanced Active Registration system
- Sophisticated media handling up to 12 paper trays
- Paper Logic for fast and easy paper orientation
- Easy to use graphical user interface
- Scalability and flexibility for investment protection
- Print operations can expand services to include ultra high volume applications such as books, course materials, training & technical manuals, booklets, catalogs, variable data printing, and transpromotional printing.

Technology

Printer type

- LED, (600 x 600 dpi) or (600 x 1,200 dpi), 85/106/125/141/180 lpi

Engine technology

- Océ Gemini Instant Duplex technology for simultaneous duplex printing in a single pass

Production

Monthly duty cycle

- Océ VarioPrint 6320 Ultra: 1 million to 10 million prints
- Océ VarioPrint 6250 Ultra: 750,000 to 8 million prints
- Océ VarioPrint 6200 Ultra: 500,000 to 5 million prints
- Océ VarioPrint 6160 Ultra: 300,000 to 2.5 million prints

Print speed

- Océ VarioPrint 6320 Ultra: 306 letter duplex prints per minute
164 ledger duplex prints per minute
- Océ VarioPrint 6250 Ultra: 250 letter duplex prints per minute
132 ledger duplex prints per minute
- Océ VarioPrint 6200 Ultra: 200 letter duplex prints per minute
106 ledger duplex prints per minute
- Océ VarioPrint 6160 Ultra: 166 letter duplex prints per minute
89 ledger duplex prints per minute
- Print speed is independent of media type and weight
- Easy temporary or permanent upgradeability to higher speeds

User Interface

- Intuitive 15" color touch screen graphic user interface
- Displays critical job and system information
- Advanced job scheduler, allows for maximum productivity and queue management

Paper Input Module

- Maximum configuration: 3 paper input modules: 12 trays with a total capacity of 13,800 sheets
- Standard 4 trays, 4,600 sheets
- Paper tray capacity (80 g/m² plain paper)
 - 2 x 600 sheets
 - 2 x 1,700 sheets

Post Process Insertion:

- All trays, all sizes available for post process insertion
- All sizes between 8"x8" (203 mm x 488 mm) and 12.6"x19.2" (320 mm x 488 mm) (from all trays)

Paper weight

- From 60 - 300 g/m²

Options

- Second and third Paper Input Module
- Roll-feed, approximately 60,000 (80 g/m²/20lb bond plain paper) sheets
- Statement size support 7"x10" (178 mm x 254 mm) (optional)

High Capacity Stacker

- Capacity 6,000 (2 stacks x 3,000 sheets - 80 g/m²)
- All sizes between 8"x8" (203 mm x 203 mm) and 12.6"x19.2" (320 mm x 488 mm)
- OEM output to third-party finishing
- Maximum total stacking capacity 18,000 sheets (with optional stackers attached)

Integrated Multi-format Stapler (not shown)

- Legal/ledger corner or dual stapling
- Mixed format stapling (50 sheets)
- Stapled output capacity: 2,000 sheets

Set Finisher (optional)

- Capacity 4,000 (plain paper sheets letter - 80 g/m²)

Sizes

The following paper sizes can be stacked (and stapled) - all (custom) sizes between:
- long edge: 10.8" - 12" (275 mm - 306 mm)
- short edge: 8.2" - 8.7" (208 mm - 220 mm)

- Number of staples in a set: 1 or 2 position staple
- Stapling positions: portrait, landscape, book
- Stapling capacity: 100 sheets plain paper (80 g/m²)
 - Shorter 50 sheet staple (optional)



Scalable configurations

In today's environment, every printshop has unique requirements. That's why the Océ VarioPrint 6320, 6250, 6200 and 6160 Ultra systems are available in a variety of configurations to meet your unique needs. Choose the combination of modules that best fits your needs. Available modules include:

- Paper input module(s)
- Océ High Capacity Stacker(s)
- Set finisher
- Integrated Multi-format Stapler (not shown)

The integrated DFD interface allows these configurations to be further extended with various third-party finishing devices.

Finishing

Many online finishing options are available, including:

- Booklet making
- Perfect binding
- Document binding
- Punching

Connectivity

Supported PDLs

- PostScript 3
- PDF

- PCL 6
- IPDS (optional)
- PCL5e/PJL (optional)

Workflow support

- Automatic language sensing for PostScript, PDF and PCL 6
- Push button switching from IPDS or PCL5e/PJL to PostScript 3/PDF PCL 6
- Streaming for all PDLs
- Xerox® DigiPath® software and FreeFlow job ticket support with Océ DPLink™ software (optional)
- Kodak® SmartBoard® connectivity support with Océ KDKlink™ (optional)

Océ Workflow modules (optional)

- Océ PRISMAaccess™
- Océ PRISMAprepare™
- Océ PRISMAarchive™
- Océ PRISMAproduction®
- Océ PRISMAsatellite®
- Océ PRISMAspool™
- Océ PRISMAweb™
- Océ NetServices
- Océ Document Designer Advanced
- Océ DPconvert®
- Océ VPconvert™ (Windows & Linux)

Network hardware

- 10/100 Mb, 1Gb Ethernet network protocols
- TCP/IP
- Novell (IPX/SPX)
- SMB

Higher-level protocols

- LPR/LPD for print job submission
- Socket printing
- SNMP
 - Host resources
 - MIBII
 - Printer MIB
 - Job Monitoring MIB

Physical Data

Sound

- Stand-by 58 dB
- Running 78 dB

Power consumption

- Stand-by mode
 - 1 kW
- Running mode
 - Océ VarioPrint 6160 Ultra 4.0 kw
 - Océ VarioPrint 6200 Ultra 4.3 kw
 - Océ VarioPrint 6250 Ultra 4.4 kw
 - Océ VarioPrint 6320 Ultra 4.9 kw

Sizes and Weights:				
	Weight (Lbs.)	Length (inches)	Width (inches)	Height (inches)
Print Engine (PE)	1,496	51.2	42.1	47.4
Paper Input Module (PIM)	396	28.3	36.3	45.3
Input Interface Module	224	23	28.3	44.9
High Capacity Stacker including finisher (HCS/FIN)	638	45.4	28.2	75.9
High Capacity Stacker (HCS)	352	45.4	28.2	46

